

Mediant™ 3100

Hybrid SBC and Media Gateway

The AudioCodes **Mediant 3100 session border controller (SBC) and media gateway** is a complete connectivity solution for medium-to-large sized enterprises, contact centers and service providers.

Scaling up to 5,000 concurrent SBC sessions, the Mediant 3100 connects IP-PBXs to any SIP trunking service provider and offers superior performance in connecting any SIP to SIP environment.

In addition, the Mediant 3100 supports up to up to 64 E1/T1 spans in a 2U platform to enable versatile connectivity between TDM and VoIP networks, such as connecting legacy TDM PBX systems to IP networks and IP-PBXs to the PSTN.



**5,000 SBC Sessions | 64 E1/T1 Spans | Extensive Vocoder Support |
Certified for Microsoft Teams Direct Routing with local media optimization**



Comprehensive interoperability

Proven interoperability with SIP trunks, unified communications solutions, PBXs and IP cloud services



Hybrid functionality

True hybrid SBC and gateway platform for gradual migration to IP communications, low CAPEX and reduced space and power footprints



Enhanced security

Robust perimeter defense against cyber, DoS and DDoS attacks, as well as eavesdropping, fraud and service theft



Superior voice quality

Advanced capabilities for optimizing and monitoring voice service quality



High resiliency

Local branch survivability and PSTN fallback

Specifications

Capacities			
Max. Signaling	5,000	Max. RTP/SRTP Sessions	5,000
Max. Registered Users	20,000	Max. Transcoding Sessions	3,200
Telephony Interfaces			
Digital PSTN Protocols	Various ISDN PRI protocols such as EuroISDN, North American NI-2, Lucent™ 4/5ESS, Nortel™ DMS-100 and others.		
PSTN	8 to 64 E1/T1 interfaces		
Network Interfaces			
Ethernet	8 GE interfaces configured in 1+1 redundancy or as individual ports		
Security			
Access Control	DoS/DDoS line rate protection, bandwidth throttling, dynamic blacklisting (Intrusion Detection System)		
VoIP Firewall	RTP pinhole management, rogue RTP detection and prevention, SIP message policy, advanced RTP latching		
Encryption/Authentication	TLS, DTLS, SRTP, HTTPS, SSH, client/server SIP Digest authentication, RADIUS Digest		
Privacy	Topology hiding, user privacy		
Traffic Separation	VLAN/physical interface separation for multiple media, control and OAMP interfaces		
Interoperability			
SIP B2BUA	Full SIP transparency, mature and broadly deployed SIP stack, stateful proxy mode		
SIP Interworking	3xx redirect, REFER, PRACK, session timer, early media, call hold, delayed offer and more		
Registration and Authentication	SIP Registrar, registration on behalf of users/servers, SIP Digest access authentication		
Transport Mediation	Mediation between SIP over UDP/TCP/TLS/WebSocket, IPv4/IPv6, RTP/SRTP (SDES/DTLS)		
Header Manipulation	Add/modify/delete SIP headers and message body using simple WireShark-like language with powerful capabilities such as variables and utility functions		
Number Manipulations	Ingress and egress digit manipulation		
Transcoding and Vocoders	Coder normalization including transcoding, coder enforcement and re-prioritization, extensive vocoder support: G.711, G.723.1, G.726, G.729A/B, GSM-FR, AMR-NB/WB, Opus-NB/WB, SILK-NB/WB		
Signal Conversion	DTMF/RFC 2833/SIP, T.38 fax, packet-time conversion		
WebRTC Gateway	Interworking between WebRTC endpoints and SIP networks. Supports WebSocket, Opus, VP8 video coder, lite ICE, DTLS, RTP multiplexing, secure RTCP with feedback.		
NAT	Local and far-end NAT traversal for support of remote workers		
Voice Quality and SLA			
Call Admission Control	Limit number and rate of concurrent sessions and registers per peer for inbound and outbound directions		
Packet Marking	802.1p/Q VLAN tagging, DiffServ, TOS		
Standalone Survivability	Maintains local calls in the event of WAN failure. Outbound calls can use PSTN fallback (including E911).		
Voice Monitoring and Enhancement	Transrating, RTP-XR, acoustic echo cancellation, replacing voice profile due to impairment detection, fixed and dynamic voice gain control, packet loss concealment, dynamic programmable jitter buffer, silence suppression/comfort noise generation, RTP redundancy, broken connection detection		
Direct Media	Hair-pinning (no media anchoring) of local calls to avoid unnecessary media delays and bandwidth consumption		
Test Agent	Ability to remotely verify connectivity, voice quality and SIP message flow between SIP UAs		
SIP Routing			
Routing Criteria	Incoming SIP trunk, DID ranges, host names, any SIP headers, codecs, QoE, bandwidth		
Querying External Databases	Routing based on customized queries of ENUM, LDAP, HTTP server (REST API)		
Route To	Configured SIP peers, registered users, IP address, request URI		
Advanced Routing Features	Alternative routes, load balancing, least-cost routing, call forking, E911 emergency call detection and prioritization		
SIPREC	IETF standard SIP recording interface		
Management			
OAM&P	Browser-based GUI, CLI, SNMP, INI Configuration file, REST API, EMS		
Physical/Environmental			
Dimensions	2U high 19-inch rack wide (H x W x D) 88 x 438 x 490 mm (3.5 x 17.24 x 19 inches)		
Weight	11.5 kg (25.3 lbs.) for fully-populated chassis		
Operating Temperature	Operational: 0° - 40° C (41° - 104° F) Storage: -25° - 70° C (-13° - 158° F) Humidity: 5% - 90% non-condensing		
Power	Redundant Dual Feed, 100-240 V AC/9-4A, 50-60Hz or 48VDC 18A max International Headquarters		



International Headquarters
 1 Hayarden Street, Airport City
 Lod 7019900, Israel
 Tel: +972-3-976-4000
 Fax: +972-3-976-4040

AudioCodes Inc.
 80 Kingsbridge Rd,
 Piscataway, NJ 08854
 Tel: +1-732-469-0880
 Fax: +1-732-469-2298

Contact us: www.audiocodes.com/contact
 Website: www.audiocodes.com

©2022 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, What's Inside Matters, OSN, SmartTAP, User Management Pack, VMAS, VoIPerfect, VoIPerfectHD, Your Gateway To VoIP, 3GX, VocaNom and AudioCodes One Voice are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.